



A6000 - Interior Alkyd Primer

Technical Specifications

PRODUCT DESCRIPTION

A6000 ProSeries Interior Alkyd Primer is a pure Soya Alkyd primer exhibiting excellent sealing and stain blocking characteristics for application in most residential or commercial environments. A6000 ProSeries is specifically formulated to seal most common interior stains and will adhere tenaciously to a variety of surfaces.

SPECIFICATIONS

Type:	Soya Alkyd	Dry Time – Touch:	2 to 4 hours
Sizes:	1's and 5's	Dry Time – Recoat:	8 to 12 hours
Bases:	None available	Full Service:	14 days
Flash Point:	41 ⁰ C (TCC)	VOC:	347 grams/liter.
Gloss:	0 to 5% at 60 ⁰ 0 to 5% at 85 ⁰	% Solids Vol:	54 – 55
		Weight Per Gallon:	11.66 +/- .25 lbs.

PRODUCT USE

Surface Preparation

Free surface of all contaminants such as dirt, dust, oil, grease, wax, and rust. Patch holes and cracks, sand smooth and remove sanding dust and spot prime.

New Wood: Sand entire surface and apply one coat of C² ProSeries Interior Alkyd Primer. Allow primer to dry. If necessary, sand surface again before applying the topcoat.

Painted Surfaces: Remove all loose or peeling paint. Repair damaged surfaces and sand smooth. Dull glossy surfaces. Spot prime with C² ProSeries Interior Alkyd Primer. When painting over dark colors, best results are achieved by priming entire surface.

New Plaster & Drywall: Plaster must be completely cured (30 days) before painting. Sand smooth drywall and tape joints and other repaired areas. Apply one coat C² ProSeries Interior Alkyd Primer to entire surface.

Application

A6000 ProSeries Interior Alkyd Primer may be applied by roller (no more than 3/8-inch nap), brush (pure china bristle) or spray.

Spreading Rate: Product may be applied at a rate of 400 to 450 square feet per gallon (37 to 42 square meters per 3.78 liters).

Thinning: Do not thin.

Airless Spray: Use a 12 to 15 mil size tip.

Cleanup: Clean painting equipment and spills immediately using mineral spirits.

Limitations: Do not apply if product, air or surface temperature is below 50⁰ F (10⁰ C) - Keep product from freezing. Product application and surface conditions are beyond the manufacturer's control. Liability, if any, is limited to replacement of product only.

Disposal: Do not dispose of any paint product or solvent in drains, sewers or municipal garbage. If disposal is necessary, contact your local municipality.

C² ProSeries Paint is formulated without lead or mercury

Last Update – July 26, 1999. (Spec A6000)