



A9000- Exterior Alkyd Primer

Technical Specifications

PRODUCT DESCRIPTION

A9000 ProSeries Exterior Alkyd Primer is a pure Soya Alkyd Primer exhibiting excellent sealing and stain blocking characteristics for application in most residential or commercial environments. A9000 ProSeries is specifically formulated to seal most common exterior stains and will adhere tenaciously to a variety of surfaces.

SPECIFICATIONS

Type:	Pure Soya Alkyd	Dry Time – Touch:	2 to 4 hours
Sizes:	1's and 5's	Dry Time – Recoat:	8 to 12 hours
Bases:	None available	Full Service:	14 days
Gloss:	0 to 5% at 60 ⁰	Flash Point:	41 ⁰ C (TCC)
	0 to 5% at 85 ⁰	VOC:	347 grams/liter
		% Solids Vol:	54 – 55
		Weight Per Gallon:	11.66 +/- .25 lbs.

PRODUCT USE

Surface Preparation

Free surface of all contaminants such as dirt, dust, oil, grease, wax, and rust. Remove mildew using a chlorine bleach solution of 1 to 4 ratio of bleach to water. Patch holes and cracks, sand smooth and remove sanding dust.

New Wood: Sand smooth and remove dust. Spot Prime all knots with C² ProSeries Exterior Alkyd Primer. Apply one coat of C² ProSeries Exterior Alkyd Primer to entire surface.

Painted Surfaces: Remove loose and peeling paint. Dull glossy areas. Apply one coat of C² ProSeries Exterior Alkyd Primer.

Application

A9000 ProSeries Exterior Alkyd Primer may be applied by roller (no more than 3/8-inch nap), brush (pure china bristle) or spray.

Spreading Rate: Product should be applied at a rate of 400 to 450 square feet per gallon (37 to 42 square meters per 3.78 liters).

Thinning: Do not thin.

Airless Spray: Use a 12 to 15 mil size tip.

Cleanup: Clean painting equipment and spills immediately using mineral spirits.

Limitations: Do not apply if product, air, or surface temperature is below 50⁰ F (10⁰ C) - Keep product from freezing. Product application and surface conditions are beyond the manufacturer's control. Liability, if any, is limited to replacement of product only.

Disposal: Do not dispose of any paint product or solvent in drains, sewers, or municipal garbage. Use all of the paint you purchase or give it to someone who can use it. If disposal is necessary, contact your local municipality.

C² ProSeries Paint is formulated without lead or mercury

Last Update – June 2, 1999. (Spec A9000)