



C2000 - Interior Latex Primer

Technical Specifications

PRODUCT DESCRIPTION

C2000 ProSeries Interior Latex Primer is a pure acrylic emulsion primer exhibiting excellent sealing and stain blocking characteristics for application in most residential or commercial environments. **C2000 ProSeries** is specifically formulated to seal most common interior stains and will adhere tenaciously to a variety of surfaces.

SPECIFICATIONS

Type:	Co-Polymer Acrylic	Dry Time – Touch:	30 minutes
Sizes:	1's and 5's	Dry Time – Recoat:	2 to 4 hours
Bases:	Not available	Full Service:	14 days
Gloss:	3 to 4% at 60 ⁰ 4 to 6% at 85 ⁰	Flash Point:	None
		VOC:	29 grams/liter.
		% Solids Vol:	35-36
		Weight per Gallon:	12.50 +/- .25 lbs.

PRODUCT USE

Surface Preparation

Clean surface to remove contaminants such as dirt, dust, oil, grease, wax, and rust. Patch holes and cracks, sand smooth and remove sanding dust and spot prime.

New Plaster & Drywall: Plaster must be completely cured (30 days) before priming. Sand smooth drywall tape joints and other repaired areas. Apply one coat **C² ProSeries Interior Latex Primer** to entire surface.

New Wood: Sand entire surface and apply one coat of **C² ProSeries Interior Latex Primer**. Allow primer to dry. If necessary, sand surface again before applying the topcoat.

Previously Painted Surfaces: Remove all loose or peeling paint. Repair damaged surfaces and sand smooth. Dull glossy surfaces. Spot prime with **C² ProSeries Interior Latex Primer**. When painting over dark colors, best results are achieved by priming entire surface.

Application

C2000 ProSeries Interior Latex Primer may be applied by roller (no less than 3/8-inch nap), brush (synthetic) or spray.

Spreading Rate: Product should be applied at a rate of 400 to 450 square feet per gallon (37 to 42 square meters per 3.78 liters).

Thinning: Do not thin.

Airless Spray: Use a 12 to 15 mil size tip.

Cleanup: Clean painting equipment and spills immediately using warm soapy water.

Limitations: Do not apply if product, air or surface temperature is below 50⁰ F (10⁰ C) - Keep product from freezing. Product application and surface conditions are beyond the manufacturer's control. Liability, if any, is limited to replacement of product only.

Disposal: Do not dispose of any paint product or solvent in drains, sewers or municipal garbage. Use all of the paint you purchase or give it to someone who can use it. If disposal is necessary, contact your local municipality.

C² ProSeries Paint is formulated without lead or mercury



C2000 - Interior Latex Primer

Technical Specifications