



C2100 - Interior Latex Flat

Technical Specifications

PRODUCT DESCRIPTION

C2100 ProSeries Interior Latex Flat is an acrylic fortified low odor, scrubable finish for application in most residential or commercial environments. C2100 ProSeries is specifically formulated to provide maximum coverage, spatterless application, and virtually *invisible touchup*.

SPECIFICATIONS

Type:	Co-Polymer Acrylic	Dry Time – Touch:	30 minutes
Sizes:	1's and 5's	Dry Time – Recoat:	2 to 4 hours
Bases:	White, Pastel, Midtone, Accent	Full Service:	14 days
Gloss:	0 to 2% at 60 ⁰ 0 to 3% at 85 ⁰	Flash Point:	None
		VOC:	77 grams/liter.
		% Solids Vol:	35 – 36
		Weight Per Gallon:	11.25 +/- .25 lbs.

PRODUCT USE

Surface Preparation

Clean surface to remove contaminants such as dirt, dust, oil, grease, wax, and rust. Patch holes and cracks, sand smooth and remove sanding dust and spot prime.

New Plaster & Drywall: Plaster must be completely cured (30 days) before painting. Sand smooth drywall tape joints and other repaired areas. Apply one coat C² ProSeries Interior Latex Primer to entire surface. Finish with one or two coats of C² ProSeries Interior Latex Flat.

Previously Painted Surfaces: Remove all loose or peeling paint. Repair damaged surfaces and sand smooth. Dull glossy surfaces. Spot prime with C² ProSeries Interior Latex Primer. When painting over dark colors, best results are achieved by priming entire surface. Finish with one or two coats of C² ProSeries Interior Latex Flat.

New Wood: Sand entire surface and apply one coat of either C² ProSeries Interior Latex or Alkyd Primer. Allow primer to dry. Sand smooth entire surface. Apply one or two coats of C² ProSeries Interior Latex Flat.

Application

C2100 ProSeries Interior Latex Flat may be applied by roller (no less than 3/8 inch nap), brush (synthetic) or spray.

Spreading Rate: Product should be applied at a rate of 400 to 450 square feet per gallon (37 to 42 square meters per 3.78 liters).

Thinning: Do not thin.

Airless Spray: Use a 12 to 15 mil size tip.

Cleanup: Clean painting equipment and spills immediately using warm soapy water.

Limitations: Do not apply if product, air or surface temperature is below 50⁰ F (10⁰ C) - Keep product from freezing. Product application and surface conditions are beyond the manufacturer's control. Liability, if any, is limited to replacement of product only.

Disposal: Do not dispose of any paint product or solvent in drains, sewers or municipal garbage. Use all of the paint you purchase or give it to someone who can use it. If disposal is necessary, contact your local municipality.

C² ProSeries Paint is formulated without lead or mercury