



C3000 - Exterior Latex Primer

Technical Specifications

PRODUCT DESCRIPTION

C3000 ProSeries Exterior Latex Primer is a pure acrylic emulsion primer exhibiting excellent sealing and stain blocking characteristics for application in most residential or commercial environments. C3000 ProSeries is specifically formulated to seal most common exterior stains and will adhere tenaciously to a variety of surfaces.

SPECIFICATIONS

Type:	Pure Acrylic	Dry Time – Touch:	30 minutes
Sizes:	1's and 5's	Dry Time – Recoat:	2 to 4 hours
Bases:	Not Available	Full Service:	14 days
Packaged Colors:	None Available	Flash Point:	None
Gloss:	10 to 15% @ 60°	VOC:	124 grams/liter
	20 to 30% @ 85°	% Solids Vol:	35 - 36
		Weight Per Gallon:	10.83 +/- .25 lbs.

PRODUCT USE

Surface Preparation

Free surface of all contaminants such as dirt, dust, oil, grease, wax, and rust. Remove mildew using a chlorine bleach solution of 1 to 4 ratio of bleach to water. Patch holes and cracks, sand smooth and remove dust.

New Wood: Sand smooth and remove dust. Spot prime knots with C² ProSeries Exterior Alkyd Primer. Apply one coat of C² ProSeries Exterior Latex Primer to entire surface. Note: For severely tannin staining woods, multiple coats of primer may be required.

Painted Surfaces: Remove loose and peeling paint. Dull glossy areas. Apply one coat of C² ProSeries Exterior Latex Primer.

Galvanized Metal: Clean surface thoroughly using a strong solvent. Apply one coat of C² ProSeries Exterior Latex Primer.

Masonry: New masonry must be fully cured (90 days). Fill blocks if required. Apply one coat of C² ProSeries Exterior Latex Primer.

Application

C3000 ProSeries Exterior Latex Primer may be applied by roller (no less than 3/8-inch nap), brush (synthetic) or spray.

Spreading Rate: Product should be applied at a rate of 400 to 450 square feet per gallon. (37 to 42 square meters per 3.78 liters)

Thinning: Do not thin.

Airless Spray: Use a 12 to 15 mil size tip.

Cleanup: Clean painting equipment and spills immediately using warm soapy water.

Limitations: Do not apply if product, air or surface temperature is below 50° F (10° C) - Keep product from freezing. Product application and surface conditions are beyond the manufacturer's control. Liability, if any, is limited to replacement of product only.

Disposal: Do not dispose of any paint product or solvent in drains, sewers or municipal garbage. Use all of the paint you purchase or give it to someone who can use it. If disposal is necessary, contact your local municipality.

C² ProSeries Paint is formulated without lead or mercury