



C4150 - Interior Latex Ceiling Paint

Technical Specifications

PRODUCT DESCRIPTION

C4150 Latex Ceiling Paint is an acrylic fortified low odor, flat finish for application in most residential or commercial environments. C4150 Interior Latex Ceiling Paint is specifically formulated to provide maximum coverage, spatterless application, and virtually *invisible touchup*.

SPECIFICATIONS

Type:	Co-Polymer Acrylic	Dry Time – Touch:	30 minutes
Sizes:	1's and 5's	Dry Time – Recoat:	2 to 4 hours
Bases:	White	Full Service:	14 days
Gloss:	0 to 2% at 60 ⁰ 0 to 3% at 85 ⁰	Flash Point:	None
		VOC:	33 grams/liter.
		% Solids Vol:	35 – 36
		Weight Per Gallon:	11.25 +/- .25 lbs.

PRODUCT USE

Surface Preparation

Clean surface to remove contaminants such as dirt, dust, oil, grease, wax and rust. Patch holes and cracks, sand smooth and remove sanding dust and spot prime.

New Plaster & Drywall: Plaster must be completely cured (30 days) before painting. Sand smooth drywall tape joints and other repaired areas. Apply one coat C² ProSeries Interior Latex Primer to entire surface. Finish with one or two coats of C² Interior Latex Ceiling Paint.

Previously Painted Surfaces: Remove all loose or peeling paint. Repair damaged surfaces and sand smooth. Dull glossy surfaces. Spot prime with C² ProSeries Interior Latex Primer. When painting over dark colors, best results are achieved by priming entire surface. Finish with one or two coats of C² Interior Latex Ceiling Paint.

New Wood: Sand entire surface and apply one coat of either C² ProSeries Interior Latex or Alkyd Primer. Allow primer to dry. Sand smooth entire surface. Apply one or two coats of C² Interior Latex Ceiling Paint.

Application

C4150 Interior Latex Ceiling Paint may be applied by roller (no less than 3/8-inch nap), brush (synthetic) or spray.

Spreading Rate: Product should be applied at a rate of 400 to 450 square feet per gallon (37 to 42 square meters per 3.78 liters).

Thinning: Do not thin.

Airless Spray: Use a 12 to 15 mil size tip.

Cleanup: Clean painting equipment and spills immediately using warm soapy water.

Limitations: Do not apply if product, air or surface temperature is below 50⁰ F (10⁰ C) - Keep product from freezing. Product application and surface conditions are beyond the manufacturer's control. Liability, if any, is limited to replacement of product only.

Disposal: Do not dispose of any paint product or solvent in drains, sewers, or municipal garbage. Use all of the paint you purchase or give it to someone who can use it. If disposal is necessary, contact your local municipality.

C² ProSeries Paint is formulated without lead or mercury